VASA Adhesive Products

HIGHLIGHTS

VASA PSA99:

A very aggressive, high-tack transitional adhesive that installs as a PSA but firms as it cures to form permanent bond.



- Compatible with a wide range of resilient and carpet tiles
- Flexible installation methods – Wet Set and Pressure Sensitive
- Maximum moisture tolerance of 99% RH / 12lb MVER
- Superior shear strength
- Ideal for environments with heavy traffic or rolling loads
- Durability with reduced floor movement
- Easy to use and easy to clean
- Apply with a trowel or roller
- Spreads opaque white and dries clear
- Includes green tracers
- FloorScore* and CRI Certified

VASA WBA:

A superior-grade solvent-free adhesive specifically designed for interior installation of wall base.

- Non-staining formula with superior green grab to keep corners wrapped tight
- Rapid set-up for fast, easy installation
- Strong initial grab for holding wall base
- Bonds with gypsum drywall, brick, concrete block, wood, properly cured plaster and concrete
- Coverage up to 240 linear feet per gallon

PSA Transitional	**Moisture Resistance**	**Shelf Life 2 Years**	**Superior Green Grab**

DESCRIPTION

VASA Adhesive Products are formulated for the installation of resilient flooring including Luxury Vinyl Tile (LVP), Luxury Vinyl Plank (LVP) and Vinyl Composite Tile (VCT), Carpet tile, as well as vinyl, rubber and carpet wall base. Our current portfolio includes firm set transitional pressure sensitive adhesive VASA PSA99 and high-performance solvent-free wall base adhesive VASA WBA. All our products are of high resistance to moisture with low odor and VOC (<1 g/L). Our formulation utilizes cutting-edge technology to fight against the growth of stains and odor-causing bacteria that usually cause product degradation. All our products are CRI certified.

PERFORMANCE

Products	**VASA PSA99**	**VASA WBA**
Color:	Off white with green tracers	Tan
Odor:	Very mild	mild, sweet odor, odorless when dries
Permanent	Wet-Set Method	
Open Time:	Up to 20 minutes	Up to 10 minutes
Working Time:	Up to 40 minutes	Up to 30 minutes
Releasable	Full-Tack Method	
Tack Time:	Up to 60 minutes	N/A
Working Time:	12 hours	N/A
Curing Time:	24 -48 hours	24 hours
Traffic:		
Residential	0 min (PSA), 12 hours (semi-wet)	N/A
Commercial:	4 hours	N/A
Rolling Loads:	24 hours	N/A
pH:	Must not exceed 12	7 - 10
VOC:	<1 g/L	<1 g/L
Setup time will vary slightly based on trowel notch, temperature, humidity, moisture and porosity of substrate.		
Shelf Life: 2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning		
Storage: While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 20°F (-6.7°C).		

Website: www.oyhglobal.com
Address: 7840 North Sam Houston Pkwy W, Houston, TX 77064